



Wireless RF Test Enclosures

JRE 0612AC 'Clamshell' Style RF Shielded Test Enclosure

Tall, wide opening enclosure with expanded size I/O plate

- Roomy 11.5 x 4.5 x 10.5 inches inside, 290 x 115 x 265 mm
- Interchangeable I/O plate with other JRE enclosures
- Adjustable latch ensures tight RF shielding
- Rugged welded aluminum construction
- Dual hinges for secure closure
- Excellent RF Isolation at a low cost: \$945

The JRE0612AC with its unique 'clamshell' style construction allows easy entry to the enclosure while still maintaining the excellent RF isolation that JRE test is known for. Using our standard sized I/O plate, there is plenty of room to allow a wide variety of connectors to be utilized. These plates are easily changed and allow one to use the same enclosure for a multitude of different I/O configurations.



Featuring rugged welded aluminum construction, you can be assured of its tight RF shielding effectiveness. Long life door gasket material along with double edge engagement not only provides solid RF shielding, but smooth trouble free operation over its lifespan.

FEATURES & BENEFITS

- Double contact cover shields ensures repeatable measurements
- 3/4" thick RF absorbing foam deadens standing waves
- Heavy duty cover latch assure tight RF isolation
- Rugged welded aluminum construction for long life
- Wide variety of connector options for every use
- Low entry configuration fits well on benchtop

CONNECTORS

Two universal I/O plates with incredible connector options. Easily changed in the field for multiple uses. JRE Test "B" size I/O plate.

ISOLATION

-100dB @ 1GHz, -95dB @ 3GHz, -85dB @ 6GHz

DIMENSIONS

Outside: 13" H x 6" W x 12" D - 330 x 150 x 300 mm
 Inside: 11.5" H x 4.5" W x 10.5" D - 290 x 115 x 265 mm



Unit shown with populated I/O plate for illustrative example

JRE 0612AC I/O Interfaces

RF Feedthru: BNC, TNC, SMA, SMB, UHF, Type-N, reverse SMA

High Performance RF Filtered Interfaces: USB2-1, USB2-2, LAN-1 Ethernet

Fiber optic: Fiber optic bulkhead feed thru: Type ST, FC.

Connector covers: Dust cover caps with tether chains included for all RF connectors

RF filtered data connectors: DB9, DB15, DB25, DB37, DB50, RJ11, RJ45, USB (Choice of 100 or 1000 pf filtering on data lines)

Power connection: 4 or 6 terminal barrier strip, 2500 pf filtering. 120/240 VAC power strip

Cover interlock switch: safety switch contact

JRE Test, LLC 7940 Rae Blvd. Victor, NY 14564
www.jretest.com 888-430-3332 sales@jretest.com